

# SWV66400 Series

## 64 Channels Digital Video Optic Transceiver

### Features

1. 8-bit digitally encoded and non-compression broadcast quality video transmission
2. Directly compatible with NTSC, PAL, and SECAM CCTV camera systems and support RS-232, RS-422, and RS-485 data protocols
3. Support any high-resolution video signal
4. Automatic compatible PAL, NTSC and SECAM video system
5. Power supply and other parameter state indication, which can monitor the operation condition of system
6. Support no-damage regenerative trunk of video
7. Constant input optical power, and large dynamic range ,no Electrical or Optical Adjustments Required .
8. Special ASIC design .
9. Industry-grade of operating temperature from -10°C to 65°C , which is applied to the different working environment
10. Hot-swap function
11. 19''4U rack-mount chassis.



### Introduction

3onedata fiber-optic video transceivers SWV66400 series can simultaneously transmit 64 channels of 8-bit digitally encoded broadcast quality video/return or bidirectional data/unidirectional or bidirectional audio/Ethernet/Telephone/Dry contact over one multimode or single-mode optical fiber. These multiplexers are typically used in applications where the cameras have P/T/Z capabilities. Plug and Play design ensures the ease of installation and operation. Electronic and optical adjustments are never required. LED indicators are provided for instantly monitoring system status. Devices are available for either standalone or rack-mount installation, which is suitable for different working environment.

### Specification

#### Technical Specification

Video channels: **64 channels**  
 Video bandwidth: 8 MHz  
 Automatic compatible video system: PAL, NTSC, SECAM  
 Video input/output impedance: 75 Ω(unbalance)  
 Video signal-to-noise ratio: ≥67dB  
 Differential gain: (10%-90%APL) DG <1% ( typical value)  
 Differential phase: (10%-90%APL) DP <0.7° ( typical value)  
 Video connector: BNC

#### Fiber-optic Specification

F/O connector: FC/ST/SC  
 TX : Power:-15 ~ -8dBm Sensitivity :≤-35dBm  
 RX: Power:-15 ~ -8dBm Sensitivity :≤-35dBm  
 Transmission Distance :20KM (single mode)  
 Operating Wavelength: TX1310/RX1550nm (Transmitter);  
 TX1550/RX1310nm (Receiver)

#### Specification of custom-made options

##### 1. Data

##### Connector: Terminal Blocks

Encoded type : RS485 / RS422 / RS232 / Manchester  
 Data rate : 0 - 400Kbps  
 BER: ≤10<sup>-9</sup>

##### 2. Audio

##### Connector: Terminal Blocks

Audio input / output impedance :600Ω(Balance/ unbalance)  
 Audio input / output voltage :2Vp-p ( typical value)  
 Audio input / output level :0dBm ( typical value)  
 Video bandwidth:10HZ~12KHZ  
 Audio digital encoded bandwidth :24bit  
 Audio signal-to-noise ratio: S/N≥95dB (weighted)

##### 3. Telephone

##### Connector: RJ11

Bandwidth :8KHZ

Features: Support call-showing function ;support H-F

Operating mode : Point to point hotline mode / FXS-FXO

#### 4. Ethernet

**Connector: RJ45**

Support mode : Half duplex or Full duplex

Standards: IEEE802.3

Data rate : 10M / 100Mbps

Bandwidth: 25M

#### Characteristic

Dimensions: 48.3(L)×22(W)×4.4(H) cm(19"1U)

Operating Voltage: AC96-240V

Operating Temperature: -10°C to +65°C

Storing Temperature: -45°C to +85°C

Humidity: 0 to 95% non-condensing

MTBF: ≥ 10<sup>5</sup> hours

**Warranty: 3 years**

**Approvals: FCC,CE, RoHS approvals**

## Application

1. Intelligent Transportation System
2. Connection of Sub-network for Surveillance Center
3. Public Security Surveillance
4. High Way & Toll Station Surveillance
5. Industrial Closed Circuit Television Surveillance

## Packing List

1. SWV66400 series digital video optic transceiver×1
2. User manual ×1
3. 220V power line ×1